

Overview

BURRO Verde is our purpose-built solution for autonomous transport to and from greenhouses. Verde seamlessly moves from narrow, congested indoor pathways to outdoor roadways, and back through the course of your workday. It can be deployed as both a towing or carrying vehicle, reducing the need for manual transport using tractors, gators or golf carts.

Verde is a collaborative robot designed to be used by farmworkers. As with all BURRO robots, Verde is built to be practical, durable, and easy-to-use.



Dimensions & Weight

LENGTH 58.3 in (148.1 cm)	HEIGHT 54in (137.2 cm)
WIDTH 27.50 in (69.8 cm)	PAYLOAD AREA 27 (cm) x 47.825 (121.48 cm) Slatted Steel Tray
WEIGHT 460lb (182 Kg)	

Carrying & Towing Capacity

MAX CARRYING PAYLOAD¹ 500 lbs (226 kg)	MAX TOWING PAYLOAD² 2000 lb
---	--

¹Rated for concrete/asphalt. Up to 750 lbs (340 kg) allowable on mud/gravel

²Will vary based on speed, terrain, and carrying/towing payload

Power & Range

MOTORS
4 x Right angle drive brushed motors

PEAK POWER
5.2 hp (3.88 kW)

CONTINUOUS TORQUE
92.7 ft-lb (125.68 Nm)

PEAK TORQUE
323.8 ft-lb (439 Nm)

MAX SPEED⁴
4.8 mph

BATTERY
2.4 kWh / 24V

BATTERY RANGE⁵
10 mi (16km)

OPERATING TEMPERATURE
-4°F to 113°F (-20°C to 45°C)

CHARGE TIME
8 hours

CHARGING INPUT
100-240 VAC, 50-60Hz: 8-10A at 120 VAC, 4-5A at 240 VAC

CHARGING OUTPUT
Onboard: 24VDC, 13A

CHARGING TEMPERATURE
32°F to 122°F (0°C to 50°C)

⁴ BURRO Verde can go up to this speed. Autonomy, load, and field conditions can/ will reduce its maximum speed

⁵ Additional batteries can be added for extended range. Will vary based on speed, carrying/towing payload, and terrain (type & grade)

Wheels & Tires

WHEEL

6" split rim (2-13/16" Bolt pattern)

TIRE⁶

R1, 14 x 4.5-6 in; Tube - 13 x 5-6

TIRE PRESSURE

15 psi (xx kPa)

⁶This is the standard/default tire for BURRO Verde. Alternative tire options can be available in the future

Computing & Sensors

CAMERA SYSTEM

4 x Stereo Camera (12 Cameras in Total)

GPS

RTK (NTRIP Compatible)

LIDAR

3D LiDAR

MODEM

4G LTE Modem

CPU & GPU

All Computing Onboard/Local

RAM

32 GB

STORAGE

256 GB SSD

COOLING

Zero-ingress Forced-Air Cooling System

Interface & Safety Features

SCREEN

7" LCD Touch Monitor

BRIGHTNESS

1000 nits

RESOLUTION

1024 x 600

BUMPER BAR/SAFETY EDGE

Front & Rear

REMOTE VIEW

Online dashboard view: See robot on map, what it's doing, and what it's seeing

VISUAL

Strobe safety running light (LED; hard-wired); Front & Rear LEDs provide cues & safety/area lighting

AUDIO

Cues inform users of Burro's autonomy & when it's in motion; Adaptive Horn: Volume adjusted based on ambient noise when in motion

Autonomy

PERSON FOLLOWING

Vision Based

AUTONOMOUS ROUTES (TEACH & REPEAT)

Vision + GPS + LiDAR

DOCKING

Vision + GPS + LiDAR

ROW NAVIGATION + ROW TO ROW

Vision Based

ATLAS (ONLINE ROUTE CREATION & MANAGEMENT + DESTINATION BASED NAVIGATION)

GPS + LiDAR

OBSTACLE HANDLING (STOPPING & AVOIDANCE/PATH PLANNING)

Vision + LiDAR

CROP SCOUTING

Vision Based

DATA COLLECTION

Up to 1 TB/hour

